



บริษัท เอดีดี เฟอร์เนส จำกัด
ADD FURNACE CO.,LTD.

44 ซอยบรมราชชนนี 70 ถนนบรมราชชนนี แขวงศาลาธรรมสพน์ เขตทวีวัฒนา กรุงเทพฯ 10170

โทร: 02-888-3472 โทร(ออกแบบ): 08-08-170-170 แฟกซ์: 02-888-3258

<https://www.add-furnace.com> E-mail: sales@add-furnace.com

BRAMA



Solenoid Valves





บริษัท เอดีดี เฟอร์เนส จำกัด ADD FURNACE CO.,LTD.

44 ซอยบรมราชชนนี 70 ถนนบรมราชชนนี แขวงศาลาธรรมสพน์ เขตทวีวัฒนา กรุงเทพฯ 10170

โทร: 02-888-3472 โทร(ออกแบบ): 08-08-170-170 แฟกซ์: 02-888-3258

<https://www.add-furnace.com> E-mail: sales@add-furnace.com

EG25... Series

Gas solenoid valves with 3/4", 1" connections and operating pressure up to 500 mbar.



Type	Nominal Diameter	P max (mbar)	Q(*)	Orifice diameter (mm)	Connections	Consumption
EG25*S.1	DN20	100	15	25	G 3/4"	20VA
EG25*SR.1	DN20	100	15	25	G 3/4"	20VA
EG25*L.1	DN20	50	15	25	G 3/4"	25VA
EG25*S.3	DN20	500	15	25	G 3/4"	36VA
EG25*SR.3	DN20	500	15	25	G 3/4"	36VA
EG25*L.3	DN20	350	15	25	G 3/4"	36VA
EG30*S.2	DN25	350	23	30	G 1"	36VA
EG30*SR.2	DN25	350	23	30	G 1"	36VA
EG30*L.2	DN25	200	23	30	G 1"	36VA
EG30*S.5	DN25	500	23	30	G 1"	37VA
EG30*SR.5	DN25	500	23	30	G 1"	37VA
EG30*L.5	DN25	350	23	30	G 1"	37VA

Q(*) Nominal flow rate in m³/h referred to ΔP 2,5mbar (δr=0,5545)

NB: for technical characteristics and overall dimensions please refer to Data Sheet 2707

Version with adjuster and motordriven modulation

EG30*M.2	DN25	350	23	30	G 1"	36VA
EG30*M.5	DN25	500	23	30	G 1"	37VA

Q(*) Nominal flow rate in m³/h referred to ΔP 2,5mbar (δr=0,5545)

NB: for technical characteristics and overall dimensions please refer to Data Sheet 12213